

Hazard Alert

Three point linkage connections



Government
of South Australia
SafeWork SA

Summary of incident

A worker was injured while clearing a log from beneath a slasher attached to a tractor via a three point linkage.

A chain and two D-shackles were used as the top link between the tractor and slasher to provide a flexible connection for rough terrain. A pin had fallen out of a D-shackle and the slasher dropped onto the worker as he removed the obstruction.

Three point linkages are commonly used to fit attachments behind tractors. The D-shackle pins had not been secured with a split pin or similar fastening device but had remained secure due to the distortion of the pin caused by the load.



A three point linkage is a standardised mechanism consisting of an adjustable top link centred above two lower lifting links.

Possible causes

- The D-shackle pin worked loose during normal machine operation as there was no secondary fastening system in place.

Action required

- Never work or stand under suspended machinery unless it is supported by suitably designed props or stands. Do not use wood to support the machinery.
- Also consider the following:
 - Ensure all persons are aware that they are not to position themselves under suspended loads.
 - Replace chain connections with an adjustable bar or some other method where possible.
 - If a chain must be used secure all D-shackle pins with a secondary fastening device.

Disclaimer | While care has been taken to ensure the accuracy and currency of the information in this publication, at the time of reading it may not be sufficiently accurate, current or complete to suit your individual needs. Reliance on the information in this publication is at your own risk. SafeWork SA accepts no liability for any loss resulting from your reliance on it. To best meet your work health and safety obligations refer to current Acts, Regulations and Approved Codes of Practice.

safe, fair, productive working lives

1300 365 255
safework.sa.gov.au
facebook.com/safeworksa

FEB 2012
HA0011-1